

FOREST

GLOBALFLOR® REALISM is made of 100% virgin material, and it doesn't contain radioactive elements and formaldehyde. Treating the flooring surface with PUR reinforcement not only improves the excellent wear-resistance performance but also helps reduce bacteria and the passage of infection. This helps promote a fresh healthy environment. REALISM is not only for use in residential areas, but also for commercial use, public areas such as hospital offices, sports facilities, schools and supermarkets.

FOREST^[1]

DESCRIPTION^[2]

Total thickness	EN 428	mm	3.0~5.0
Wear Layer	EN 429	mm	0.1~0.5
Size	EN 427	-	6"*36" / 12"*24"

CLASSIFICATION

European classification	EN 685	Class	23/34
Fire rating	EN 13501-1:2007	Class	B _{fl} -s1
Slip resistance	DIN 51130	Class	R9

PERFORMANCE

Dimension stability (80°C, 6h)	EN 434	%	0.1
Warp (80°C, 6h)	EN 434	mm	±0.5
Castor chair test	EN 425		No disturbance
Residual indentation	EN 433	mm	<0.1
Mildew resistance	ASTM G21	-	Level 1
Toxicity	EN 71-3	-	Pass
Corrosion resistance	EN 423	-	Level 0
Gloss	-	gu	±2



[1] Globalflor has a policy of continuous product and product data improvement, it reserves the right to change design and specifications without notice. For the latest TDS, please kindly check www.bomeiflor.com

GLOBALFLOR
Powered By
BOMEIFLOR